

MASK6-W

6.5" design two-way loudspeaker,
white



The MASK6 is a 6.5" two-way low impedance loudspeaker with timeless design. This full range loudspeaker has been designed for the contractor market and delivers crystal clear sound, from background music up to 'dance level' music. It can of course be used with a subwoofer when higher power is needed. MASK6 loudspeakers are suitable for both indoor and outdoor use (IP64 rating).

Thanks to the Intelli-Mount bracket, the MASK6 is easy and fast to install. The Vari-throat horn for the tweeter and the 5° down tilt angle in which the woofer and tweeter are mounted in the cabinet, guarantee a perfect sound dispersion, without the need of a big tilt angle of the cabinet itself. The MASK6 cabinet has a M12 thread mounting point tapped at the back of the cabinet, in this way a lot of other mounting systems can be used.

The cabinet of MASK6 is made of high quality enforced PP4 ABS and the grille is made of aluminium. The internal bracketing and the shape of the cabinet avoid internal interference and optimise the sound quality of the MASK6 loudspeaker. The loudspeaker has a coated 6.5" paper cone woofer and a 1" silk dome tweeter.

Its phase alignment and wide frequency range makes sure every note, starting from the robust bass over the clean middle range to the crystal clear highs, reaches your ears with an astonishing clarity.

The built-in Auto-Reset 3-step Protection Guard together with the quality components makes MASK6 a fail-safe loudspeaker, even at high power loads!

TECHNICAL SPECIFICATIONS

height in mm	315	width in mm	175
depth in mm	195	loudspeaker system	2-way
woofer size in inch	6,5	woofer cone material	coated paper
tweeter size in inch	1	mounting system	intellimount
colour	black / white	impedance (ohms)	8
low impedance dynamic power in watts	200	SPL 1W/1m in dB	90
max SPL 1m in dB	110	frequency response in Hz	60 - 20K
main construction material	ABS plastic	grille main material	aluminium
IP rating	64	Horizontal dispersion angle 1000 Hz	180°
Vertical dispersion angle 1000 Hz	180°	Net weight product (kg)	3,60

[MORE PICTURES](#)



ACCESSORIES

**MASKW-W**

Double V-shaped cluster bracket for MASK4(T)-W/MASK6(T)-W

**MASKV-W**

V-shaped 2-way cluster bracket for MASK4(T)-W / MASK6(T)-W

**MASKL-W**

L-shaped side bracket for MASK4(T)-W / MASK6(T)-W